


Stabilized Telehandlers

Regulatory area: EU

P30.10



MODEL	P30.10	P30.10L
A - Length (mm)	4700	4700
C - Wheelbase (mm)	2740	2740
F - Ground clearance (mm)	290	290
H - Width (mm)	2100	2100
M - Cab width (mm)	1010	1010
P - Height (mm)	2120	2020
S - Fork steering range (mm)	5050	5050

MODEL	P30.10	P30.10L
PERFORMANCE		
Unladen weight (kg)	7600	7600
Maximum load capacity (kg)	3000	3000
Lift height (m)	9.8	9.8
Maximum reach (m)	6.7	6.7
Boom side-shift (mm)	—	—
Frame levelling (%)	—	—
Boom section	3	3
POWERTRAIN		
Engine	REHLKO 2504	REHLKO 2504
Range/Cylinders (l)	2.5/4	2.5/4
Engine power (kW/HP)	55.4/75.1	55.4/75.1
Anti-pollution technology	Stage V - DOC + DPF	Stage V - DOC + DPF
Reversible Fan	●	●
Maximum speed (km/h)	40	40
Fuel tank capacity (l)	80	80
AdBlue tank capacity (l)	—	—
Hydrostatic transmission EPD	●	●
Electronic joystick	●	●
Axles	Axial	Axial
Brakes	Dry discs	Dry discs
HYDRAULIC		
Delivery / pressure (bar-l/min)	117-210	117-210
Hydraulic oil tank capacity (l)	85	85
CAB		
ASCS	Light	Light
FOPS/ROPS Cab	●	●
Tilting cab	—	—
CONFIGURATION		
Hydropneumatic Suspension CS Merlo	—	—
Frame suspension	—	—
Permanent four-wheel drive	●	●
Three steering way	●	●
Standard tyres	400/70-20"	400/70-20"
Hydraulically controlled stabilizers	Narrow	Narrow
Turret rotation	—	—
PTO (rpm)	—	—
3-point rear linkage (kg)	—	—

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com
Release 24/03/2026 - 9:19

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.