


Stabilized Telehandlers

Regulatory area: EU
P50.18



MODEL	P50.18PLUS	P50.18CSTOP
A - Length (mm)	6190	6190
C - Wheelbase (mm)	3060	3060
F - Ground clearance (mm)	485	485
H - Width (mm)	2480	2480
M - Cab width (mm)	1010	1010
P - Height (mm)	2535	2535
S - Fork steering range (mm)	5611	5611

MODEL	P50.18PLUS	P50.18CSTOP
PERFORMANCE		
Unladen weight (kg)	13300	13650
Maximum load capacity (kg)	5000	5000
Lift height (m)	17.5	17.5
Maximum reach (m)	13.5	13.5
Boom side-shift (mm)	+/- 445	+/- 445
Frame levelling (%)	+/- 8	+/- 8
Boom section	4	4
POWERTRAIN		
Engine	PERKINS 904	PERKINS 904
Range/Cylinders (l)	3.6/4	3.6/4
Engine power (kW/HP)	85.9/116.8	100/136
Anti-pollution technology	Stage V - SCR + DOC + DPF	Stage V - SCR + DOC + DPF
Reversible Fan	●	●
Maximum speed (km/h)	40	40
Fuel tank capacity (l)	140	140
AdBlue tank capacity (l)	16	16
Hydrostatic transmission EPD	●	●
Electronic joystick	●	●
Axles	Drop portal	Drop portal
Brakes	Dry discs	Dry discs
HYDRAULIC		
Delivery / pressure (bar-l/min)	108-250	139-250
Hydraulic oil tank capacity (l)	110	110
CAB		
ASCS	Full	Full
FOPS/ROPS Cab	●	●
Tilting cab	—	—
CONFIGURATION		
Hydropneumatic Suspension CS Merlo	—	●
Frame suspension	—	—
Permanent four-wheel drive	●	●
Three steering way	●	●
Standard tyres	400/80-24"	400/80-24"
Hydraulically controlled stabilizers	Narrow	Narrow
Turret rotation	—	—
PTO (rpm)	—	—
3-point rear linkage (kg)	—	—

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.
Via Nazionale, 9
12010 S. Defendente di Cervasca, (Cuneo) Italia
Tel. +39 0171 614111
info@merlo.com www.merlo.com
Release 25/02/2026 - 9:10

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.